

SHIELDCOAT TECHNICAL DATA SHEET

FLOORSHIELD



DESCRIPTION

Floorshield is a revolutionary, eco-friendly water-based acrylic/urethane blend sealer that outperforms traditional solvent-based options. With minimal odor and self-priming capabilities on most surfaces, it is ideal for both DIY enthusiasts and professionals. Floorshield offers superior adhesion, even to old coatings. It can also be enhanced with Shieldcoat's Anti-Slip for added safety, achieving a P4 wet slip rating. Perfect for re-coating driveways, patios, and more. Floorshield sets new industry standards.

Available in various colors with a Low Sheen finish.

4 Gallon Pails


Note: Floorshield is not recommended for steep driveways or paths as it can become slippery when wet, even with anti-slip added. For such cases, consider our STEP SAFE KIT. Floorshield is self-priming on most surfaces, but a primer may be needed for porous concrete.




APPLICATION GUIDE

- Stir the product thoroughly before use.
- Make sure the substrate is clean and free from any contamination, such as dirt, dust, or oils.
- Apply the first coat evenly using a roller for large areas and a brush for edges. Let it dry (2-4 hours).
- Apply a second coat within 6-12 hours of the first. Can also be sprayed on using a 519 tip or similar.
- For enhanced safety, mix Shieldcoat's Anti-Slip Wax Beads with the product for added traction.


FLOORSHIELD



SELF
PRIMING



ADVANCED
ADHESION



WATER
BASED

COVERAGE: Up to 807 sqft / pail

SOLIDS: 40% ave.

WFT: 100um

DFT: 40um

TOUCH DRY: 2 Hours

FOOT TRAFFIC: 4-6 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT