

SHIELDCOAT TECHNICAL DATA SHEET

RUSTSHIELD

W

DESCRIPTION




Rustshield W is a high-performance, water-based acrylic sealer and primer designed for metal roof substrates. It offers superior protection against rust and provides an ideal base for Thermobond IR or Thermobond HRC topcoats. With over 12 years of proven durability, Rustshield W outperforms traditional solvent-based primers and spot treatments. When used with Thermobond IR or Thermobond HRC, it comes with a 12-year guarantee for long-lasting protection.

Viscous liquid - Dries grey

Available in 4 Gallon pails

APPLICATION GUIDE

- Rustshield W is ready to use, with no thinning required, however if desired thin with water sparingly.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 44.6°F or above 95°F.
- Rustshield W is designed to be airless sprayed using a 521 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

RUSTSHIELD W	COVERAGE: 970 sqft per pail SOLIDS: 50% ave WFT: 180um DFT: 90um TOUCH DRY: 30 Mins RECOAT: 2 Hours SHELF LIFE: 24 Months CLEAN UP: Water		
 ADVANCED ADHESION	 WATER BASED	 MAXIMUM COVERAGE	 HIGH OPACITY

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT