

SHIELDCOAT TECHNICAL DATA SHEET

SHIELDSEAL W PLUS

DESCRIPTION

Shieldseal W Plus is an innovatively designed primer, engineered specifically for chalky metal or other previously unpainted metal roofing materials. Shieldseal W Plus can also be used on asbestos roofs to help bind and encapsulate loose surface fibres, providing a more stable surface prior to the application of compatible coating systems. With it's phenomenal adhesion capabilities achieved through a thin tack coat, this product sets a new standard in the primer industry. Coverage is exceptional, stretching up to 1,937 square feet per pail, providing unparalleled value. Formulated for quick application, Shieldseal W Plus makes the prep work fast and efficient, allowing you to move on to the finishing coats sooner.

Milky liquid - Dries clear

Available in 4 Gallon pails

APPLICATION GUIDE

- Shieldseal W Plus is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 44.6°F or above 95°F.
- Shieldseal W Plus is designed to be airless sprayed using a 517 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

<h2>SHIELDSEAL W PLUS</h2>		COVERAGE: 1,937 sqft per pail	
		SOLIDS: 20% ave	
		WFT: 90um	
		DFT: 20um	
		TOUCH DRY: 20 Mins	
		RECOAT: 2 Hours	
		SHELF LIFE: 24 Months	
		CLEAN UP: Water	

**ADVANCED
ADHESION**

**QUICK
DRY**

**MOULD
RESISTANT**

**DRINKING
WATER SAFE**

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT