

SHIELDCOAT TECHNICAL DATA SHEET

SHIELDSEAL W

DESCRIPTION




Shieldseal W is a clear penetrating primer designed to provide excellent adhesion and surface preparation across a wide range of roofing substrates, including asphalt shingles, clay tiles, concrete roof tiles and other porous roof surfaces. Fast-drying and easy to apply, Shieldseal W penetrates deep into the substrate to promote maximum adhesion and provide a sound base for subsequent coating systems.

Milky liquid - Dries clear

Available in 4 Gallon Pails

APPLICATION GUIDE

- Shieldseal W is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 44.6°F or above 95°F.
- Shieldseal W is designed to be airless sprayed using a 517 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

<h2>SHIELDSEAL W</h2>	<p>COVERAGE: 1,130 sqft per pail</p> <p>SOLIDS: 22% ave</p> <p>WFT: 140um</p> <p>DFT: 30-35um</p> <p>TOUCH DRY: 20 Mins</p> <p>RECOAT: 2 Hours</p> <p>SHELF LIFE: 24 Months</p> <p>CLEAN UP: Water</p>
<div><p>DRIES CLEAR</p></div> <div><p>PENETRATES</p></div> <div><p>MOULD RESISTANT</p></div> <div><p>DRINKING WATER SAFE</p></div>	

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT