

SHIELDCOAT TECHNICAL DATA SHEET

STEP SAFE WB PRIMER

DESCRIPTION

Step Safe WB Primer is a clear, water-based acrylic primer formulated to penetrate and consolidate porous concrete substrates. It assists in sealing surface porosity, reducing uneven absorption and promoting optimum adhesion of subsequent Step Safe Heavy Duty, Step Safe Roll On and Floorshield coating systems.

Available in 4 Gallon pails


Note: Shieldcoats Step Safe Heavy Duty WB Primer should be applied using a roller, not a sprayer to ensure maximum surface contact and penetration. Rolling helps the primer work into the pores of the concrete, improving mechanical adhesion and overall bond strength for the top coats.




APPLICATION GUIDE

- Stir the product thoroughly before use.
- Make sure the substrate is clean and free from any contamination, such as dirt, dust, or oils.
- Apply a small amount to an inconspicuous area to ensure compatibility and check for any adverse reactions
- Apply first coat with a lambswool roller or soft-bristle broom and let it dry for at least 2 hours in good weather.


STEP SAFE HEAVY DUTY WB PRIMER



SELF
PRIMING



ADVANCED
ADHESION



MAXIMUM
COVERAGE

COVERAGE: Up to 538 sqft/ pail

SOLIDS: 25% ave.

WFT: 80um

DFT: 15um

TOUCH DRY: 30 Mins

FOOT TRAFFIC: 24 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT