

SHIELDCOAT TECHNICAL DATA SHEET

STEP SAFE WB SEALER

DESCRIPTION

Step Safe WB Sealer is a clear, water-based acrylic sealer formulated to protect and enhance coated concrete surfaces. It forms a durable protective film that improves resistance to moisture, staining and general wear, while providing a uniform sealed finish over Step Safe Roll On and Step Safe Heavy Duty coating systems.

Available in 4 Gallon pails


****Note:** Shieldcoat Step Safe WB Sealer may be applied using either a hopper gun or roller. Apply the sealer evenly across the surface to achieve a consistent protective film and uniform finish. Ensure adequate and even coverage to maximise surface protection, durability and overall coating performance.




APPLICATION GUIDE

- Stir the product thoroughly before use.
- Make sure the substrate is clean and free from any contamination, such as dirt, dust, or oils.
- Apply 1-2 coats with a lambswool roller or a hopper gun.
- Let it dry for at least 2 hours in good weather.


STEP SAFE HEAVY DUTY WB SEALER



SELF
PRIMING



ADVANCED
ADHESION



MAXIMUM
COVERAGE

COVERAGE: Up to 538 sqft/ pail

SOLIDS: 25% ave.

WFT: 80um

DFT: 15um

TOUCH DRY: 1 Hour

FOOT TRAFFIC: 24 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT